


	T mm	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25										
Ø		0,236	0,276	0,315	0,354	0,394	0,433	0,472	0,512	0,551	0,591	0,630	0.669	0.709	0.748	0,787	0,827	0,866	0,906	0,945	0,984										
16"	406,4	59,2	68,9	78,6	88,2	97,8	107,3	116,7	126,1	135,5	144,8																				
18"	457,2	66,8	77,7	88,6	99,5	110,3	121,0	131,8	142,4	153,0	163,6	174,1																			
20"	508,0	74,3	86,5	98,6	110,8	122,8	134,8	146,8	158,7	170,6	182,4	194,1																			
22"	558,8	81,8	95,3	108,7	122,0	135,3	148,6	161,8	175,0	188,1	201,2	214,2																			
24"	609,6	89,3	104,0	118,7	133,3	147,9	162,4	176,9	191,3	205,6	220,0	240,1											255,2	270,2	285,2						
26"	660,4	96,8	112,8	128,7	144,6	160,4	176,2	191,9	207,6	223,2	238,7	254,3											269,7	285,2	300,5	315,9					
28"	711,2	104,3	121,6	138,7	155,9	172,9	189,9	206,9	223,8	240,7	257,5	274,3											291,0	307,7	324,3	340,9					
30"	762,0	111,9	130,3	148,8	167,1	185,5	203,7	222,0	240,1	258,3	276,3	294,4											312,3	330,3	348,1	366	383,8				
32"	812,8		139,1	158,8	178,4	198,0	217,5	237,0	256,4	275,8	295,1	314,4											333,6	352,8	371,9	391,0	410,1				
34"	863,6		147,9	168,8	189,7	210,5	231,3	252,0	272,7	293,3	313,9	334,4											354,9	375,4	395,8	416,1	436,4	456,6			
36"	914,4			178,8	201,0	223,0	245,1	267,1	289,0	310,9	332,7	354,5	376,2	397,9	419,6	441,1	462,7	484,2	505,6	527,0											
38"	965,2			188,8	212,2	235,6	258,9	282,1	305,3	328,4	351,5	374,5	397,5	420,5	443,4	466,2	489,0	511,7	534,4	557,1	579,7										
40"	1.016,0				223,5	248,1	272,6	297,1	321,6	346,0	370,3	394,6	418,8	443,0	467,2	491,3	515,3	539,3	563,2	587,1	611,0										
42"	1.066,8				234,8	260,6	286,4	312,2	337,8	363,5	389,1	414,6	440,1	465,6	491,0	516,3	541,6	566,9	592,1	617,2	642,3										
44"	1.117,6					273,2	300,2	327,2	354,1	381,0	407,9	434,7	461,4	488,1	514,8	541,4	567,9	594,4	620,9	647,3	673,6										
46"	1.168,4					285,7	314,0	342,2	370,4	398,6	426,7	454,7	482,7	510,7	538,6	566,4	594,2	622,0	649,7	677,3	704,9										
48"	1.219,2					298,2	327,8	357,3	386,7	416,1	445,5	474,8	504,0	533,2	562,4	591,5	620,5	649,5	678,5	707,4	736,3										
50"	1.270,0					310,7	341,5	372,3	403,0	433,6	464,3	494,8	525,3	555,8	586,2	616,5	646,8	677,1	707,3	737,5	767,6										
52"	1.320,8						355,3	387,3	419,3	451,2	483,0	514,9	546,6	578,3	610,0	641,6	673,2	704,7	736,1	767,5	798,9										
54"	1.371,6						369,1	402,4	435,6	468,7	501,8	534,9	567,9	600,9	633,8	666,6	699,5	732,2	764,9	797,6	830,2										
56"	1.422,4						382,9	417,4	451,9	486,3	520,6	554,9	589,2	623,4	657,6	691,7	725,8	759,8	793,8	827,7	861,5										
58"	1.473,2							432,4	468,1	503,8	539,4	575,0	610,5	646,0	681,4	716,8	752,1	787,4	822,6	857,7	892,9										
60"	1.524,0							447,5	484,4	521,3	558,2	595,0	631,8	668,5	705,2	741,8	778,4	814,9	851,4	887,8	924,2										
62"	1.574,8								500,7	538,9	577,0	615,1	653,1	691,1	729,0	766,9	804,7	842,5	880,2	917,9	955,5										
64"	1.625,6								517,0	556,4	595,8	635,1	674,4	713,6	752,8	791,9	831,0	870,0	909,0	947,9	986,8										
66"	1.676,4								533,3	574,0	614,6	655,2	695,7	736,2	776,6	817,0	857,3	897,6	937,8	978,0	1.018,2										
68"	1.727,2									591,5	633,4	675,2	717,0	758,7	800,4	842,0	883,6	925,2	966,6	1.008,1	1.049,5										
70"	1.778,0									609,0	652,2	695,3	738,3	781,3	824,2	867,1	909,9	952,7	995,5	1.038,2	1.080,8										
72"	1.828,8									626,6	671,0	715,3	759,6	803,8	848,0	892,2	936,2	980,3	1.024,3	1.068,2	1.112,1										
74"	1.879,6										689,8	735,3	780,9	826,4	871,8	917,2	962,6	1.007,8	1.053,1	1.098,3	1.143,4										
76"	1.930,4										708,5	755,4	802,2	848,9	895,6	942,3	988,9	1.035,4	1.081,9	1.128,4	1.174,8										
78"	1.981,2										775,4	823,5	871,5	919,4	967,3	1.015,2	1.063,0	1.110,7	1.158,4	1.206,1											
80"	2.032,0											844,8	894,0	943,2	992,4	1.041,5	1.090,5	1.139,5	1.188,5	1.237,4											
84"	2.133,6												939,1	990,8	1.043	1.094,1	1.145,7	1.197,2	1.248,6	1.300,0											
88"	2.235,2													1.038	1.093	1.146,7	1.200,8	1.254,8	1.308,8	1.362,7											
92"	2.336,8													1.086	1.143	1.199,3	1.255,9	1.312,4	1.368,9	1.425,3											
96"	2.438,4													1.134	1.193	1.252,0	1.311,0	1.370,0	1.429,0	1.488,0											
100"	2.540,0													1.181	1.243	1.304,6	1.366,1	1.427,7	1.489,2	1.550,6											



**Production Range of Spiral Piles**

From hot rolled coil bending capacity of the mill

Outside Diameter 16" to 160" or 457 mm to 4.064 mm

Unit length 20' to 120' or 6 m to 37 m bevelled to 20° or 35° -0+5°

Possibility to supply flame cut ends up to 200' or 61 m

For sites with difficult access possibility to produce in situ with mobile mill

All welds performed by certified welders for reinforcing plates, heads and shoes

Welding universal interlocks compatible with U and Z type larssen infill sheet piles for combi-wall

Anticorrosion paint systems applied surface preparation by automatic shot blasting

Worldwide delivery by liner lines or chartered vessels geared or gearless with or without deck option

Technical delivery conditions as per: EN 10 219 or ASTM A 252

All welds 100% UST Level UT 4 as per EN 10246-9

Tolerances: Diameter 1% max 10 mm Length ±100 mm Thick ± 1.5 mm Out of Round. 2% Straightness 2 %

Mill test certificates delivered for piles 3.1 as per EN 10204